



## *Profiline 4-sided*

### *Secondary clock for outdoor use*

PROFILINE – a modular concept of a professional clock-line in modern design.

**Cubic execution**, four-sided, for dimensions 60 and 80 cm, with or without illumination.

The clock-case itself is characterized by a highly finished, weatherproof design in aluminium profiles, built to high professional standards for easy service and commissioning.




## PROFILINE outdoor clock 4-sided, cubic


Outdoor clock, 4-sided, cubic, ceiling or post mounting, nominal dial diameters 60 and 80 cm. With or without illuminating attachment. Weather resistant case of aluminium section, clear anodized finish. Flat mineral glass cover. White dial with black marking.

Impact resistant version (BW) available as an option.

For both diameters, two different dial types are available:



Type 300



Type 315

### PROFILINE 4-sided, cubic

#### Order reference

Example  
**PL4B.A.60.300.DA.BW**



#### Clock-type

PROFILINE, without illumination  
PROFILINE, with illumination

**PL4**  
**PL4B**

#### Movement type

Minute pulse movement, 24 to 60 V  
Minute pulse movement 24, 48 or 60 V <sup>1)</sup> with synchronous seconds 230 V / 50 Hz or 48 V / 50 Hz <sup>1)</sup>  
Radio movement with built-in DCF-antenna/reciever unit for independent battery operation  
Movement for independent self-setting clocks, DCF-77 radio receiver included  
Movement for independent self-setting clocks, DCF-77 radio receiver included, synchronous seconds 230V / 50Hz  
MOBALine-movement for operation (control and supply) as self-setting clock.  
MOBALine-movement for operation (control and supply) as self-setting clock, synchronous seconds 230V / 50Hz

**A**  
**F**  
**FWU**  
**SAA**  
**SFA**  
**SAM**  
**SFM**

#### Clock dimension

60 x 60 cm  
80 x 80 cm

**60**  
**80**

#### Dial -type

Dial with line marks, type 300  
Dial with arabic numerals, type 315

**300**  
**315**

#### Mounting

Ceiling suspension <sup>2)</sup>  
Central post mounting <sup>3)</sup>

**DA**  
**ZM**

#### Option

Impact protection

**BW**

- <sup>1)</sup> Ordering please specify impulse and connection voltage  
<sup>2)</sup> For mounting "DA" please specify length "L".  
<sup>3)</sup> For mounting "ZM" please specify pole-diameter values between 9 cm (min.), 15 cm (max.)

Dial diameter (cm) 60 80  
Width of cube "E" (cm) 850 1100

